



| | |
|--------------------------|--------------|
| Holding force [N]: | 36 |
| Voltage [VDC]: | 24 ±10% |
| Duty cycle [%]: | 100 |
| Thermal ins. Class: | E |
| Device protection: | IP65 |
| Terminal cover: | IP00 |
| Power [W]: | 6.5 |
| Device to: | DIN VDE 0580 |
| Surface protection: | Fe/Zn10 |
| Armature thickness [mm]: | 2 |

| REVISION TABLE | | | | | |
|----------------|-----|--------|------|----------|--|
| ZONE | REV | REASON | DATE | APPROVED | |
| | A00 | | | | |

| | | | | |
|---|---------|------------------------------|------|-----------------|
| Tolerance: DIN 7167 (DIN ISO 286-1) | | Material: Carbon Steel | | Weight: |
| General tolerance: DIN ISO 2768 - m | | Coating: Zn | | 12 [g] |
| UNIMAGNET s.r.o. | Drawn | Date | Name | Scale: |
| | Checked | | | |
| Na Padesátníku I 161 00 Praha 6 Česká republika | | Name: EMS-1512-24V | | Sheet: 1 / 1 |
| UNIMAGNET | | Draw. No.: EMS-1512-24V | | |
| | | Alt.name: | | |

